


ULTRABAKE™ TUBING

600°F (315°C)


Part Number	OD		ID		Coil Length	
	Ø A Imperial (in)	Metric (mm)	Ø B Imperial (in)	Metric (mm)	Feet	Meters
ST0040	0.040	1.02	0.165	4.19	100	30
ST0062	0.062	1.57	0.187	4.75	100	30
ST0080	0.080	2.03	0.205	5.21	100	30
ST0093	0.093	2.36	0.218	5.54	100	30
ST0109	0.109	2.77	0.234	5.94	100	30
ST0125	0.125	3.18	0.250	6.35	100	30
ST0140	0.140	3.56	0.265	6.73	100	30
ST0156	0.156	3.96	0.281	7.14	100	30
ST0172	0.172	4.37	0.297	7.54	100	30
ST0187	0.187	4.75	0.312	7.92	100	30
ST0203	0.203	5.16	0.328	8.33	100	30
ST0218	0.218	5.54	0.343	8.71	100	30
ST0234	0.234	5.94	0.359	9.12	100	30
ST0250	0.250	6.35	0.375	9.53	100	30
ST0281	0.281	7.14	0.406	10.31	100	30
ST0312	0.312	7.92	0.437	11.10	100	30
ST0343	0.343	8.71	0.468	11.89	100	30
ST0375	0.375	9.53	0.500	12.70	100	30
ST0406	0.406	10.31	0.531	13.49	100	30
ST0437	0.437	11.10	0.562	14.27	100	30
ST0500	0.500	12.70	0.625	15.88	100	30
ST0625	0.625	15.88	0.750	19.05	50	15
ST0750	0.750	19.05	0.875	22.23	50	15
ST0875	0.875	22.23	1.000	25.40	50	15
ST0937	0.937	23.80	1.062	26.97	50	15
ST1000	1.000	25.40	1.125	28.58	50	15
ST1125	1.125	28.58	1.250	31.75	50	15
ST1250	1.250	31.75	1.375	34.93	50	15
ST1375	1.375	34.93	1.500	38.10	50	15
ST1500	1.500	38.10	1.625	41.28	50	15
ST1625	1.625	41.28	1.750	44.45	50	15
ST1750	1.750	44.45	1.875	47.63	50	15
ST1875	1.875	47.63	2.000	50.80	50	15
ST2000	2.000	50.80	2.125	53.98	50	15



- Recommended for Powder Coating, E-Coating, Plating and Anodizing
- 1/16" wall thickness
- Ideal for round tubing stock, long studs and pins
- Flexible
- Reusable
- Extremely versatile – cut to size

ULTRABAKE™ STAR TUBING

600°F (315°C)



- Star-shaped design allows for easy removal
- Flexible enough to fit a wide range of diameters

Part Number	Color	Diameter		Coil Length	
		Imperial (in)	Metric (mm)	Feet	Meters
UST-0500	Rusty Red	0.500	12.70	100	30
UST-0750	Green	0.750	19.05	50	15
UST-1000	Blue	1.000	25.40	50	15
UST-1500	Rusty Red	1.500	38.10	50	15